

## FS082 FIXO - NON ADJUSTABLE LANYARD

The **FALL SAFE**<sup>®</sup> **FS082** - **FIXO NON ADJUSTABLE LANYARD** is a low stretch static kernmantle lanyard with high proportion of sheath to cover ratio wich provides improved abrasion protection. FS082 has heavy duty stitched ends for extra resistance.



EAN CODE	LENGTH (M)	WEIGHT (KG)
5605423730470	1,0	0,1
5605423730456	1,5	0,2
5605423730494	2,0	0,3



Rescue | Riggers | Rope access



STANDARDS

**CE** EN354:2010



# TECHNICAL DATA SHEET

#### FS082 FIXO - NON ADJUSTABLE LANYARD

FEATURES



CONNECTOR COMBINATIONS

A D F5820	B 0 1	C Q	D FS831	E FS836	H 000 FS33500-2L	K R FS826	L 0	M 6	N F5843	(T) <b>(D)</b> F5823	W F5829	(Y) F5824	
PHYSICAL	PHYSICAL PROPERTIES												
Metal parts				N/A	N/A								
Rope				Mamba negra 11mm									
+ Availab	ole sizes			0.5M, 3M, 4M, 5M									
OTHER IN	OTHER INFORMATION												
Device lifespan 10 years													
Max. Loa	d	i <100 Kg											
Inspectio	on requiren	nent		Yearly									
Traceabi	lity			Serial Number/ QR Code									
Manual Instructions				www.fal	www.fallsafe-online.com   +351 252 480 060								



## FS802 ZINC-PLATED STEEL OVAL

110mm

The FALL SAFE® FS802 - ZINC PLATED STEEL OVAL is a screw lock connector in zinc plated steel, with a 18 mm opening and a breaking strength of 25 kN.



59mm

EAN CODE	STRENGTH (kN)	OPENING (MM)	~WEIGHT (KG)		9	STANDARDS			
5605423400113	25	18	0,162	C	E	EN362:2004-B			
	IS	C	EN12275:1998-H						
Telecom towers   Rope access   Roof works   Riggers   Rescue   Construction   Arborism   Image: Construction   Arborism									
PHYSICAL PROPERTIES	PHYSICAL PROPERTIES								
Material		Zinc plated steel							
Closure		Screw lock							
OTHER INFORMATION									
Device lifespan		Indefined <sup>*</sup>							
Inspection requireme	ent	Yearly							
Traceability		Serial Number/ Batch number							
Manual Instructions	anual Instructions www.fallsafe-online.com   +351 252 480 060								

\*The product's lifetime is considered Indefined, when the products can be used until being rejected during the inspection.

FALL SAFE® - Zona Industrial da Varziela, Rua B, Lote 54, 4480-620 Vila do Conde, PORTUGAL | Tel.: +351 252 480 060 | Fax.: +351 252 480 069 | Website: www.fallsafe-online.com Copyright © 2020-2021 FALL SAFE®, All rights reserved. All pictures shown are for representation purpose only. Actual product may vary due to product enhancement. Products and specifications subject to change without notice.



### FS843 ZINC PLATED PIPE HOOK

The FALL SAFE® FS843 - ZINC PLATED PIPE HOOK is an auto lock hook in steel, with a 52 mm opening and a breaking strength of 22 kN.



235mm

EAN CODE	STRENGTH (kN)	OPENING (MM)	~WEIGHT (KG)		STANDARDS
5605423400168	22	52	0,48	CE	EN362:2004-A
	APPLICATIO	NS			
Cons	struction   Scaffolding   A	ccess platforms			
PHYSICAL PROPERTIES					
Material		Steel			
Closure		Auto lock			
OTHER INFORMATION					
Device lifespan		Indefined*			
Inspection requireme	ent	Yearly			
Traceability		Serial Numb	per/ Batch num	ber	
Manual Instructions		www.fallsafe	e-online.com  -	+351 252 480 060	

\*The product's lifetime is considered Indefined, when the products can be used until being rejected during the inspection.