

Product leaflet

Product
Filter element A3P3

Model No.
SR 292

Ordering No.
R03-2001

Product Description

The SR 292 filter element is intended for use together with Sundström compressed air filter. The filter is of type A3P3 and provide protection against:

Type A protects against oils, organic gases and vapours, such as solvents, with boiling points > +65 °C.
Type P3 protects against all types of particulate pollutants, e.g. dust, mist and smoke.

Technical specification

SR 292	
Diameter/height	115 mm/184 mm
Weight	≈ 760 g
Service temperature	-10 – +55 °C, < 90 % RH
Storage temperature	-20 – +40 °C, < 90 % RH
Filtration efficiency, Paraffin oil	> 99,993 %
Filtration efficiency, Sodium Chloride NaCl	> 99,993 %
Resistance time: ¹⁾ A3, Cyclohexane C ₆ H ₁₂ , 8 000 ppm	> 150 min

1) Internal test results



Head Office

Tel: +46-(0)8-562 370 00
Fax: +46-(0)8-562 370 20

Visiting address:
Stockholmsvägen 33
SE-181 33 Lidingö

Factory

Tel: +46-(0)8-562 370 00
Fax: +46-(0)8-562 370 60

Visiting address:
Västergatan 4
SE-341 50 Lagan

Sundström 
www.srsafety.com