

Data sheet

Set Lory PRO



GENERAL

Art. no.:	L-0697-2	E-class number:	40-02-01-90
EAN:	4030281250906	Customs no.:	84798997
Standard:	EN 358:1999		



Data sheet

Set Lory PRO

DOUBLE-O TRI/DOUBLE-O TW Model: LORY is a robust descender and belay device. Its various application areas make the Lory your reliable companion for rope access and rescue (abseiling up to 225 kg load). LORY is used for work positioning, as a restraining device at roofs or slab edges, as a temporary anchor or for fall arrest in flexible cable systems. With LORY, the belaying person can easily feed and take rope. When using the device correctly, it blocks automatically in case of a fall. The LORY PRO model with its unimpeded movement of the cam is the ideal device for industrial purposes. It is equipped with a descent handle that ensures secured and controlled abseiling. The double-stop function blocks if the handle is pulled overly in panic and provides extra safety.

EN 341: max./min. rated load: 30 - 180 kg; max. descent height: 190 m; rope diameter: 11

EN 12841-C: max. rated load: 225 kg; rope

diameter: 10-12 mm

EN 358 and EN 795: rope diameter: 10.5 / 11

mm

ANSI Z359.4-2013

FEATURES

Diameter:

10,5 mm Max. service life: 4-6 Years Max. number of persons: 1 Temperature: from -20 °C to +60 °C Suspension element: Coated core rope 10,5mm

DIMENSIONS

Size: 2m Weight: 0,78 kg

HARDWARE

Carabiner on device: DOUBLE-O TRI **DOUBLE-O TWIST** Carabiner on rope:

MATERIAL

Material:

Polyamide, Aluminium, Steel



COMPONENTS

Set of components:

1 x	Lory PRO	MAT-A-041
1 x	ROPE FOR LORY PRO	L-0685-2
1 x	DOUBLE-O TRI	H-176-TRI
1 x	DOUBLE-O TWIST	H-176-TW
1	POS-Faltschachtel Größe	MAT-2410-
Χ	1	01
1 x	GA-LORY	MAT-BA- 0173