

DATASHEET

XL-D TG



GENERAL

Art.Nr:	H-254	Standards:	EN 12275-B:2013, EN 362-B:2004
GTIN:	4030281024149	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

XL-D TG

The XL-D TG is a light-alloy hot-forged connector with large capacity base and triplex gate, ideal for the connection of multiple devices. Its enhanced H-profile provides an excellent weight-to-strength ratio. It also scores with a wide gate opening and large internal capacity. Effortless clipping is achieved by the catch-free locking system. The XL-D TG connector is also compatible with the FIX PRO+ positioning device. - Enhanced H-profile for excellent weight-to-strength ratio - Large capacity base and gate triplex - Wide gate opening and large internal capacity - Made of light-alloy

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various
Fallindicator:	No
Colour:	Silver, Red
Strengths - lengthways:	28.00 kN
Strengths - open:	10.00 kN
Strengths - across:	12.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 362:2004), Type B (EN 12275:2013)
Maximum lifetime:	30 years
Maximum temperature:	40 °C
Minimum temperature:	-30 °C
Standard ANSI:	No
Standard UIAA:	No
Anti-twist device:	No
Carabiner clasp:	Triple

DIMENSIONS

Opening width:	28 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------