

Data sheet  
**PEANUT I**



**GENERAL**

Art. no.: HSG-021-1,8-1

EAN: 4030281181897

Standard: DIN 19427:2017  
EN 360:2002  
GS-PS-12:2019  
RFU PPE-  
R/11.060:2018  
RFU PPE-  
R/11.085:2020  
RFU PPE-  
R/11.124:2020

E-class number: 40-02-01-03

Customs no.: 84798997

## Data sheet

### PEANUT I

The compact connecting device PEANUT I with FS90 ALU karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

#### FEATURES

Colour:	orange / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Facade / Window Cleaning, Fire brigade / Rescue / Special Forces, Mobile Work Platforms

## DIMENSIONS

Size:	1,8m
Weight:	1,78 kg

## HARDWARE

Carabiner on anchoring point side:  
FS 90 ALU

Carabiner on belt side: STAK TRI

## MATERIAL

Material:  
Polyester, Polyamide, Aluminium