

Data sheet
PEANUT I



GENERAL

Art. no.: HSG-021-2,5-3

E-class number: 40-02-01-03

EAN: 4030281181927

Customs no.: 84798997

Standard:

EN 360:2002
GS-PS-12:2019
RFU PPE-
R/11.060:2018
RFU PPE-
R/11.085:2020
RFU PPE-
R/11.124:2020

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ST karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 59 cm can be used variably and is extremely robust. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All shock absorber and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	grey / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Scaffolding

DIMENSIONS

Size:	2,5m
Weight:	1,96 kg

HARDWARE

Carabiner on anchoring point side:
FS 90 ST

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:
Polyester, Polyamide, Steel