

DATASHEET

D-BOLT TYP 47 (AP-058)



GENERAL

Art.Nr:	AP-TYP-47	Standards:	CEN/TS 16415,EN 795:2012-A
GTIN:	4030281277460	Net weight:	0.93 kg
E-class number:	40-02-01-90	Gross weight:	0.93 kg
Customs tariff number:	73269098		

DATASHEET

D-BOLT TYP 47 (AP-058)

The single anchor point D-BOLT AP-TYP-47 is tested and certified according to EN 795, CEN/TS 16415. It is made of quenched and tempered steel 1.0503, is yellow painted and has been specially developed for use on steel substructures. The steel substructure must comply with the expected loads of min. 14 kN. It is fastened with an M16 hexagon bolt, washer and nut (included in delivery). It can be loaded in all directions and can secure up to three persons with their PPEgA against falling.

- Single anchor point, especially for steel surfaces
- Fastening with M16 hexagon bolt, washer and nut (included in delivery), AK 1, approved for 3 persons

FEATURES

Anchor point type:	Stationary anchor point
Type mounting base:	Steel
Mounting type:	Machine screws
Application areas:	Off Shore Industry, Telco energy, Wind energy
Colour:	Yellow
Maximum number of persons:	3
Maximum load:	500.00 kg
Rope access technique:	Yes

DIMENSIONS

Diameter pillar:	13 mm
Diameter bore:	18 mm
Construction height:	80 mm
Foot plate length:	101 mm
Foot plate width:	46 mm
Hole spacing a:	23 mm
Hole spacing b:	50 mm

MATERIAL

Material:	Steel
-----------	-------